BRUNNER

# Declaration of Performance according to Regulation (EU) 305/2011

| | | |
|---|---|---|
| Product | | Iron Dog 06 |
| Intended use | | Space heating in buildings |
| Manufacturer | | Ulrich Brunner GmbH |
| Adress of the manufacturer | | Zellhuber Ring 17-18<br>84307 Eggenfelden |
| System for assessment and verification of constancy of performance of the construction product. | | System 3 |
| The notified testing laboratory has carried out initial testing according to system 3 | | |
| Notified laboratory | | 1015 |
| Test report | | 1015-AoP-30-17934/TZ |
| Harmonized technical specification | | EN 16510-2-2:2022 |
| **Essential characteristic** | | |
| **Safety in case of fire** | | |
| Protection of combustible materials | Minimum distances to combustible materials | |
| | bottom | $d_B$ = 1 mm |
| | floor in front | $d_F$ = 800 mm |
| | ceiling | $d_C$ = 1000 mm |
| | rear | $d_R$ = 250 mm |
| | side | $d_S$ = 250 mm |
| | side radiation area | $d_L$ = 600 mm |
| | adjacent combustible materials (e.g. furniture) | $d_P$ = 800 mm |
| | material type and thickness of protective insualtion material | NPD |
| **Hygiene, health and the environment** | | |
| At nominal heat output at 13% $O_2$ | Carbon monoxide emission (CO) | = 1250 mg/m3 |
| | Nitrogen oxides emissions ($NO_X$) | = 200 mg/m3 |
| | Emission of organic gaseous carbon (OGC) | = 120 mg/m3 |
| | Particulate matter emissions (PM) | = 40 mg/m3 |
| At part load heat output at 13% $O_2$ | Carbon monoxide emission (CO) | NPD |
| | Nitrogen oxides emissions ($NO_X$) | NPD |
| | Emission of organic gaseous carbon (OGC) | NPD |
| | Particulate matter emissions (PM) | NPD |
| **Safety and accessibility in use** | | |

© 2026 Brunner GmbH

| | | |
|---|---|---|
| Data for installation to a chimney at nominal heat output | Flue gas outlet temperature | 226 °C |
| | Minimum flue draught | 12 Pa |
| | Flue gas mass flow | 9,6 g/s |
| Data for installation to a chimney at part load heat output | Flue gas outlet temperature | NPD |
| | Minimum flue draught | NPD |
| | Flue gas mass flow | NPD |
| Data for installation to a chimney regarding fire safety | Fire safety of installation to the chimney | T400 G |
| **Energy economy and heat retention** | | |
| Appliance's thermal output and energy efficiency at nominal heat ouput | Space heat output | 8,7 kW |
| | Water heat output | NPD |
| | Efficiency | 81,0 % |
| Appliance's thermal output and energy efficiency at part load heat ouput | Space heat output | NPD |
| | Water heat output | NPD |
| | Efficiency | NPD |
| Space heating efficiency | Seasonal space heating efficiency | 71,0 % |
| | Energy efficiency index (EEI) | 108 |
| | Energy efficiency classification | A+ |
| | Electric power consumption at nominal heat output | NPD |
| | Electric power consumption at part load heat output | NPD |
| | Standby mode power consumption | NPD |
| **Sustainable use of natural ressources** | | |
| | Environmental sustainability | NPD |


© 2026 Brunner GmbH

The performance of the product corresponds to the declared performance.

This declaration of performance is issued under the sole responsibility of the manufacturer in accordance with Regulation (EU) No. 305/2011.

Signed for and on behalf of the manufacturer:



Eggenfelden, 13.07.2026

Hubertus Brunner, CEO

© 2026 Brunner GmbH